

## API DOCUMENTATION

- **Recharge Api(GET)**

[http://<GIVEN\\_URL>/Apirequest?userId=<GIVEN\\_USERID>&password=<GIVEN\\_PASSWORD>&tranPin=<GIVEN\\_TRANPIN>&mobile=<recharge\\_mobile\\_no>&amount=<amount>&opCode=<operatorCode>&request\\_id=<unique\\_id>](http://<GIVEN_URL>/Apirequest?userId=<GIVEN_USERID>&password=<GIVEN_PASSWORD>&tranPin=<GIVEN_TRANPIN>&mobile=<recharge_mobile_no>&amount=<amount>&opCode=<operatorCode>&request_id=<unique_id>)

**Response :-**

Success:-  
{ "rechargeStatus": "SUCCESS",  
"message": "Recharge SUCCESS. Transaction Id: sdfdsfds",  
"operatorid": "454566575676",  
"status": " SUCCESS ",  
"TransactionId": "sdfdsfds" }

Failed:-  
{ "rechargeStatus": "FAILED",  
"message": "Recharge FAILED. Transaction Id: sdfdsfds",  
"operatorid": "NA",  
"status": "FAILED",  
"TransactionId": "sdfdsfds" }

- **Utility Bill Fetch(POST form-data)**

[http://<GIVEN\\_URL>/ApirequestbillFetch?userId=<GIVEN\\_USERID>&password=<GIVEN\\_PASSWORD>&tranPin=<GIVEN\\_TRANPIN>&consumerNumber=<ConsumerNumber>&opCode=<operatorCode>&amount=0&request\\_id=<UniqueId>&consumerMobile=<consumerMobile>](http://<GIVEN_URL>/ApirequestbillFetch?userId=<GIVEN_USERID>&password=<GIVEN_PASSWORD>&tranPin=<GIVEN_TRANPIN>&consumerNumber=<ConsumerNumber>&opCode=<operatorCode>&amount=0&request_id=<UniqueId>&consumerMobile=<consumerMobile>)

**Response : -**

Success:-  
{ "Dueamount": "54", "status": "SUCCESS", "DueDate": "12/12/1989", "CUSTNAME": "test", "BILLNO": "454", " PARTIALPAYALLOW": "NO", " BILLDATE": " 12/12/1989" }

Failed:-

{ "message": "Invalid Input", "status": "FAILED" }

- **Utility bill Pay(POST form-data)**

[http://<GIVEN\\_URL>/ApirequestbillPay?userId=<GIVEN\\_USERID>&password=<GIVEN\\_PASSWORD>&tranPin=<GIVEN\\_TRANPIN>&consumerNumber=<ConsumerNumber>&opCode=<operatorCode>&amount=<amount>&consumerMobile=<consumerMobileNO>&dueDate=<recived from previous response>&request\\_id=<UniqueId>](http://<GIVEN_URL>/ApirequestbillPay?userId=<GIVEN_USERID>&password=<GIVEN_PASSWORD>&tranPin=<GIVEN_TRANPIN>&consumerNumber=<ConsumerNumber>&opCode=<operatorCode>&amount=<amount>&consumerMobile=<consumerMobileNO>&dueDate=<recived from previous response>&request_id=<UniqueId>)

Response: -

{ "operatorid" : "fg4554", "rechargeStatus": "SUCCESS", "TransactionId": "757yrtyrt" }

## PAN API

Using our PSA APIs you can request a PSA registration and can also allot the coupons to respective PSA.

API' s

1. CreateAgent
2. CouponRequest

### 1.CreateAgent(POST form-data)

Using this request you can register the PSA (PAN Card service agent)

[http://<GIVEN\\_URL>/creatAgentApi](http://<GIVEN_URL>/creatAgentApi)

#### Request Parameters

Parameter	Required	Description
psaname	MANDATORY	PSA Name
location	MANDATORY	PSA Location
pincode	MANDATORY	PSA Pincode
state	MANDATORY	PSA State
phone1	MANDATORY	PSA Phone1
phone2	MANDATORY	PSA Phone2
emailId	MANDATORY	PSA Email Id
pan	MANDATORY	PSA Pan
dob	MANDATORY	PSA Dob(dd/mm/yyyy)
aadhaar	MANDATORY	PSA Aadhaar
district	MANDATORY	District
userId	MANDATORY	Given UserId
password	MANDATORY	Given Password
tranPin	MANDATORY	Given Pin

#### **Response:-**

```
Success:-{
  "requestid": "2928",
  "message": "Agent Create Successfully",
  "status": "SUCCESS",
  "panuserid": "TEST646415641641",
  "panPassword": "TEST646415641641",}
Failed:-
{"message": <Failed Message>
```

```
"status": "FAILED"}
```

## 2. CouponRequest (POST form-data)

Use this request to Buy coupons for your PSA.

<https://<GIVEN URL>/couponrequestApi>

### Request Parameters

Parameter	Required	Description
totalcoupan	MANDATORY	Request Coupon
Panuserid	MANDATORY	Given With Final Response Of Create Agent
userId	MANDATORY	Given userId
password	MANDATORY	Given password
tranPin	MANDATORY	Given tranPin

### Response:-

Success:-

```
{  
  "message": <SUCCESS Message>,  
  "requestid": "2928",  
  "status": "SUCCESS"  
}
```

Failed:-

```
{  
  "message": <Failed Message>,  
  "status": "FAILED"  
}
```

```
}
```

